

SSP-1529
Semi-Conductive Silicone Compound

PRODUCT DESCRIPTION

SSP-1529 is a 65 durometer semi-conductive silicone compound. This product is supplied as fully cured, conductive sheet stock or ready-to-mold compound. The data below was generated using ASTM test method and procedures.

DATA	Typical Values
Shore A (60-70 range)	65
Tensile psi (500 minimum)	1000 psi
Elongation % (150 minimum)	200%
Compression Set %	7.5%
Specific Gravity	1.17
Volume Resistivity ohm / cm (10 max)	7 ohm /cm
Color	Black
Thermal Stability Range	-60°C - 220°C

STORAGE

Store in a cool, dry environment.

SHELF LIFE

The shelf life of SSP1529 is 2 months. Cold storage may extend shelf life.

HANDLING & SAFETY

MSDS information is available on request.

For more information visit www.sspinc.com. To order call **(518) 885-8826/** or Fax **(518) 885-4682**.

Specialty Silicone Products, Inc.

Corporate Technology Park * 3 McCreia Hill Road * Ballston Spa, NY 12020

Specialty Silicone Products, Inc is an ISO 9001:2008 registered company.

Because we cannot foresee or control varied conditions, under which this information and our materials may be used, we do no guarantee the applicability or accuracy of this information or the suitability of our materials for their specific purposes. This material is provided without warranty, either expressed or implied, of fitness for a specific purpose or nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license under valid patents.