



SSP1217 (TEFCONE 2)

SUPERIOR PERFORMANCE SILICONE LUBRICATING GREASE

PRODUCT DESCRIPTION

SSP1217 (TEFCONE 2) is a light bodied silicone lubricating grease, containing a high content of PTFE, designed for demanding applications where maximum surface contact is required under a wide range of loads. SSP1217 (TEFCONE 2) features an application operating range of -40°F to 400°F, non-corrosiveness, plus excellent dispersion and stability. SSP1217 (TEFCONE 2) offers superior lubrication to a wide variety of metals and non-metals, as well as corrosion resistance, as well as superior electrical insulation characteristics.

DATA	TYPICAL VALUES
Appearance	Light Yellow
Temperature	-70°F to 400° F
Unworked Penetration (230-265 Range)	250
Evaporation (< 1% after 1 hour @ 200°C)	0.30%
Specific Gravity (1.14 – 1.24 range)	1.17
Dielectric Strength (at 50 mil gap)	500 Volts / Mil
Dielectric Constant	3.0
Volume Resistivity	2.18x10 ¹⁴ ohm/cm

KEY FEATURES	APPLICATIONS	CONTAINERS
Low Volatiles Stable from -40°F - 400°F Non-corrosive Easy to handle and clean	Bi-Metal Lube Heating and Air Conditioning Fans Spark Plug Boots Plastic Lubrication Electrical Connections Garage Door Chain Drives General Purpose Marine & Automotive	400 lb Drum 40 lb Plastic Pail 8 lb. Plastic Pail 1 lb Jar 14.1 oz Cartridge 5.3 oz Plastic Tube

Private labeling & specialty packaging are always available to meet customers' total requirements.

HANDLING & SAFETY

MSDS information is available on request.

For more information visit www.sspinc.com. To order call **(518) 885-8826/** or Fax **(518) 885-4682**.

Specialty Silicone Products, Inc.

Corporate Technology Park * 3 McCrea Hill Road * Ballston Spa, NY 12020

Specialty Silicone Products, Inc is an ISO 9001:2008 registered company.

Because we cannot foresee or control varied conditions, under which this information and our materials may be used, we do not guarantee the applicability or accuracy of this information or the suitability of our materials for their specific purposes. This material is provided without warranty, either expressed or implied, of fitness for a specific purpose or nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license under valid patents.