

## DLS Electronic Systems, Inc.

Company: Specialty Silicone Products				Date: 8/30/23		
Type: SSP502-60V0 (DF036)						
Frequency MHz	OPEN Amplitude (dBuV)	SOLID PLATE Amplitude (dBuV)	Gasket Amplitude (dBuV)	Signal Generator Setting (dBm)	Shielding Effectiveness (dB)	Dynamic Range (dB)
10	100	-25	-15	15	115	125
20	110	-25	-10	16	120	135
40	115	-25	-12	10	127	140
60	115	-25	-6	3	121	140
80	115	-25	-5	-3	120	140
100	115	-25	-4	1	119	140
200	115	-25	-6	-4	121	140
400	115	-25	-4	-6	119	140
600	115	-25	-6	0	121	140
800	115	-25	-2	2	117	140
1000	115	-20	-14	-43	129	135
2000	110	-20	-13	-46	123	130
4000	110	-20	-14	-50	124	130
6000	110	-20	-15	-47	125	130
8000	110	-20	-15	-46	125	130
10000	110	-20	-14	-45	124	130
12000	110	-20	-15	-41	125	130
15000	110	-20	-16	-43	126	130
18000	110	-20	-17	-42	127	130

Shielding Effectiveness (dB) - SSP502-60V0 (DF036)

